

ETI Data System Library for COBOL/DB2 DA

Release Notes

Revision 4.2.1A

May 2003

Copyright © 2003 by Evolutionary Technologies International, Inc. All rights reserved.

Evolutionary Technologies International, ETI, ETI Solution, ETI•EXTRACT, the ETI logo, Dialogue Coach, and MetaStore are trademarks or registered trademarks of Evolutionary Technologies International, Inc.

All other product and company names mentioned are included for identification only and may be trademarks and/or registered trademarks of their respective companies or institutions.

Table of Contents

| | | |
|----------|---|-----------|
| 1 | PREREQUISITES | 3 |
| 2 | DSL INSTALLATION | 3 |
| | IF YOU HAVE ETI•EXTRACT INSTALLED..... | 3 |
| | INSTALLING THE DSL | 3 |
| 3 | INFORMATION ABOUT THIS RELEASE..... | 4 |
| 3.1 | SINGLE STEP IS DEFAULT | 4 |
| 3.2 | COBOL INTERMEDIATE ACTIONS DA 4.2 AND MERGE PROCESSING..... | 4 |
| 3.3 | SETTING THE DRIVER UNIT..... | 4 |
| 3.4 | DOCUMENTATION ADDENDUM | 4 |
| 4 | RELEASE 4.2.1..... | 4 |
| 4.1 | PURPOSE..... | 4 |
| 4.2 | IMPORTANT NOTICES | 4 |
| 4.2.1 | <i>String Equivalent of a Number Truncation Problem</i> | 4 |
| 4.2.2 | <i>Concatenating Multiple Parts</i> | 5 |
| 4.2.3 | <i>Using a CIP or Filter to Set Null Condition on Part</i> | 5 |
| 4.2.4 | <i>Filter Modifications</i> | 5 |
| 4.2.5 | <i>Update and Replace Count Changes</i> | 5 |
| 4.2.6 | <i>Lookup Return Parts Initialized When NULL</i> | 5 |
| 4.3 | FEATURES IN RELEASE 4.2.1 | 5 |
| 4.3.1 | <i>Conversion Processing</i> | 5 |
| 4.3.2 | <i>Single-Step Conversions</i> | 5 |
| 4.3.3 | <i>Multi-Step Conversions</i> | 7 |
| 4.3.4 | <i>Controlling the Type of Conversion Generated</i> | 7 |
| 4.3.5 | <i>Potential Differences in Conversion Results with Single-Step Versus Multi-Step Conversions</i> | 8 |
| 4.3.6 | <i>Select Distinct Option for Selecting Records Conditionally</i> | 8 |
| 4.3.7 | <i>New Option for Connecting as a Different User</i> | 9 |
| 4.3.8 | <i>COBOL Intermediate Actions DA 4.2</i> | 9 |
| 4.3.9 | <i>Setting the Driver Unit</i> | 10 |
| 4.4 | ISSUES ADDRESSED IN RELEASE 4.2.1 | 10 |
| 5 | RELEASE 4.2.0..... | 11 |

1 PREREQUISITES

This DSL requires the following products to be at the indicated release number *or later*:

- **ETI•EXTRACT® Tool Suite Release 4.2.2p4** or **ETI Solution™ Version 5.0.3**. Required to ensure that the DSL will generate the expected code.
- **Shared Objects 4.2.5**. This component will be loaded automatically during the installation of the DSL when you select the option to auto-load the prerequisites.
- **TCL Functions 4.2.2**. This component will be loaded automatically during the installation of the DSL when you select the option to auto-load the prerequisites.
- **COBOL Intermediate Actions 4.2.1**. Required for supporting enhanced merge processing. This component will be loaded automatically during the installation of the DSL when you select the option to auto-load the prerequisites.

2 DSL INSTALLATION

If You Have ETI•EXTRACT Installed

To install ETI Data System Libraries, follow the directions in the manuals listed below, depending on the version of the software you are using:

For ETI•EXTRACT Tool Suite Release 4.2.2:

- Windows: *ETI•EXTRACT Tool Suite: Installation Guide for Windows*, Chapter 10, “Installing Data System Libraries”
- UNIX: *ETI•EXTRACT Tool Suite: Installation Guide for UNIX*, Chapter 6, “Installing Data System Libraries”

For ETI Solution Version 5.x:

- *ETI Solution Administration Guide*, Chapter 3, “Installing and Loading ETI Data System Libraries”

Warning: If you do not follow the DSL installation procedures described in the manuals listed above, but instead manually copy files from the CD-ROM, then you will not get the updated version of the DSL install script, which will cause the DSL installation to fail.

Installing the DSL

With the new DSL patch process, a DSL can be shipped with any available patches. To install the DSL simply follow the normal procedure for installing a DSL. If patches are available you will be prompted to load the patches; answer “yes”.

3 INFORMATION ABOUT THIS RELEASE

3.1 Single Step is Default

Beginning with Release 4.2.1, the DSL for COBOL/DB2 DA is designed to generate single-step conversion programs by default if at all possible. See the section “Conversion Processing” on page 5 for details.

3.2 COBOL Intermediate Actions DA 4.2 and Merge Processing

Releases 4.2.1 (or greater) of ETI•EXTRACT and COBOL Intermediate Actions DA 4.2.1 (COBOL/IA DA 4.2.1) provide better control on how data is merged than in previous releases of the DSL. This can mean existing conversions may exhibit different behavior when the DSL for COBOL/DB2 DA is installed. Refer to the section “COBOL Intermediate Actions DA 4.2” on page 9 for information on the differences in merge processing.

3.3 Setting the Driver Unit

Setting the driver unit is typically no longer necessary. Refer to the section “Setting the Driver Unit” on page 10 for information.

3.4 Documentation Addendum

The *ETI Data System Library DA: Documentation Addendum* contains documentation errata and updates since the release of the *ETI Data System Library DA: Procedures* and *ETI Data System Library DA: Reference* manuals. You should review the addendum for this information.

4 RELEASE 4.2.1

4.1 Purpose

The primary purpose of this release is to support single-step conversion processing and provide fixes for issues reported in prior releases.

4.2 IMPORTANT NOTICES

Installing this release may require program re-generation and a validation of existing conversions with the conditions described in this section. You should review the following conditions to see if they are applicable to your conversions.

4.2.1 String Equivalent of a Number Truncation Problem

In previous releases, performing the String Equivalent of a Number incorrectly truncated the result to the length of the target part prior to processing. The result was that intermediate filter functions could not act upon the complete string equivalent of the number when the size of the target part was less than the size of the source part. This has now been fixed.

4.2.2 Concatenating Multiple Parts

In previous releases, concatenating multiple parts together such that the result would be greater than 22 characters produced results being truncated to 22. This has now been fixed.

4.2.3 Using a CIP or Filter to Set Null Condition on Part

In previous releases, when using a CIP or a filter to set the null condition on a part in the query program, the null condition was incorrectly handled by the merge program and not being written to the output ifile. This has now been fixed.

4.2.4 Filter Modifications

Several filters have been modified to correct reported filter problems. You must run the **ex_fixFilters.pl** utility to scan your conversion and fix these invalid filters. The **ex_fixFilters.pl** utility is located in the MetaStore's™ dsl/bin directory. Refer to the documentation for **ex_fixFilters.pl** in the “Miscellaneous Documentation” section of the *ETI Data System Library DA: Documentation Addendum* for description and usage. You should run this utility whenever you are migrating MetaStores or upgrading DSLs.

4.2.5 Update and Replace Count Changes

Update and replace counts are now maintained and reported in separate messages (ETI220 and ETI221 respectively). Previously the update and replace counts were maintained and reported in one message (ETI220).

4.2.6 Lookup Return Parts Initialized When NULL

Lookup return parts are now initialized when NULL. Previously, the lookup return part was not initialized when NULL and as a result, the part value contained the value of the previous part.

4.3 Features in Release 4.2.1

4.3.1 Conversion Processing

By default, ETI•EXTRACT attempts to generate conversions with the fewest number of execution steps (conversion programs) possible. Minimizing the number of execution steps simplifies the work of the user, as there are fewer steps to execute, monitor, and verify.


A single-step conversion is usually more efficient than a multi-step conversion. However there are constraints that must be met for ETI•EXTRACT to be able to generate a single-step conversion. There may also be cases when you will get the most efficient solution by forcing ETI•EXTRACT to generate a multi-step conversion.

4.3.2 Single-Step Conversions

With single-step conversions, ETI•EXTRACT generates the following:

- a subroutine that queries the source database(s) and merges the data as required
- a main populate routine that calls the query subroutine and populates the target databases

The generation of a single executable program eliminates the I/O operations required to pass the data through intermediate files and programs. A simplified illustration of the flow of data is shown in the following diagram:



Since a single conversion program runs on one computer, the execution of the conversion is simple and easy to manage.

If ETI•EXTRACT determines that a single-step conversion is not possible, it generates a multi-step conversion.

4.3.2.1 Requirements for Single-Step

A single-step conversion can be generated when:

- One source and one target database object were created using the same installation object.
 - An installation object represents a Data Access System (DAS), (coboldb2_da, for example) running on a particular host computer. Therefore, all source and target databases must use the same DAS and be running on the same host.
- Source and target database must be one physical DB2 database.
- The business rules for the conversion can be processed in a single-step.
- ETI•EXTRACT has determined there is no need to write data to an ifile. If ifiles are needed, then single-step is not possible.

4.3.2.2 Message Program Information

ETI•EXTRACT writes messages to three files with the following names:

- <conversion_name><instruction_name>.log
- <conversion_name><instruction_name>.wrn
- <conversion_name><instruction_name>.err

where <conversion_name> is either the name or an abbreviation of the name of the conversion and <instruction_name> is the name of the instruction that wrote the message (or an abbreviation of the instruction name).

In single-step conversions there is one executable program and one set of message files. In that case the instruction is populate1. For example, the message files for the single-step conversion SSCONV would be called:

- SSCONVpopulate1.log
- SSCONVpopulate1.wrn
- SSCONVpopulate1.err

4.3.2.3 Overview of Differences between Pre-DA Single-Step and DA Single-Step

Please refer to the section “Differences with Pre-DA Single-Step” in the *ETI Data System Library DA: Procedures* manual, in Chapter 15 “Single-Step and Multi-Step Conversions”.

4.3.3 Multi-Step Conversions

With a multi-step conversion, there is at least one executable query instruction and one executable populate instruction. Data passes through at least one ifile. A multi-step conversion may or may not require separate intermediate actions (separate executable instructions for sorting and merging data) and associated ifiles.

4.3.4 Controlling the Type of Conversion Generated

This section describes how you can generate different types of conversions.

4.3.4.1 Generating Single-Step Conversions

ETI•EXTRACT will automatically generate a single-step conversion when possible.

4.3.4.1.1 Reasons to Generate a Single-Step Conversion

A single-step conversion typically offers several advantages over a multi-step conversion:

- faster throughput
- lower disk space requirements
- less CPU usage
- simpler execution plans

These advantages result from the fact that a single-step conversion program will not pass data through any intermediate files (ifiles). Multi-step conversions using individual programs create one or more ifiles, written to disk, for subsequent processing by intermediate action programs and by the final populate programs.

Using a single-step conversion may prove most advantageous when you:

- are converting very large files
- have limited disk space

A multi-step conversion may require that you perform the conversion in phases because it:

- takes too long to execute, due to the time it takes to read and write ifiles
- limits the number of records that you can convert at one time due to ifile size limitations

There are times, however, when you may want to generate a multi-step conversion instead of a single-step, as described below.

4.3.4.2 Generating Separate Query and Populate Programs with Ifiles

Set the value of `ifile_io` to `true` to generate a multi-step with ifiles and separate query and populate programs with the merge included within the query instruction.

4.3.4.2.1 Reasons to Generate Separate Query and Populate Programs with Ifiles

You might want to do this when:

- The ifiles will be used as input to a non-ETI process, outside of the ETI•EXTRACT conversion.
You should use caution if you use ifiles for this purpose. Subtle changes in the conversion specification will cause the ifiles to change. If you are relying on the ifile data to be consistent over time, this might be a problem.
- You want to be certain that the query has worked satisfactorily before executing the populate.

4.3.5 Potential Differences in Conversion Results with Single-Step Versus Multi-Step Conversions

4.3.5.1 Spaces In Source Data Fields

In multi-step conversions, source data fields that contain all spaces are treated as null when they are written to the ifiles and when they are written to the target data files.

With single-step conversions, since they do not use the ifile system, fields that contain all spaces on the source are written to the target with all spaces.

For additional information about single- and multi-step conversions, refer to Chapter 15 “Single-Step and Multi-Step Conversions” in the *ETI Data System Library DA: Procedures* manual.

4.3.6 Select Distinct Option for Selecting Records Conditionally

A new **Select distinct** option has been added for selecting records conditionally for the Read operations.

The **Select distinct** option uses the DISTINCT clause to remove all duplicate values for the mapped parts read. A usage example is shown below.

Sample Results for Select Records:

Alabama
Alabama
Arkansas
California
California

Sample Results for Select **Distinct** Records:

Alabama
Arkansas
California

Notice that with the **Select distinct** option, *no* duplicate part names are returned.

4.3.7 New Option for Connecting as a Different User

A new option for connecting to a DB2 database using a particular userid and password has been added. Two new properties have been created to accomplish this:

- `shell_db2_pwd` — specifies the DB2 password to use when accessing a database
- `shell_db2_uid` — specifies the DB2 user ID to use when accessing a database

Please refer to Chapter 1 of the *ETI Data System Library DA: Reference* manual for additional information.

4.3.8 COBOL Intermediate Actions DA 4.2

4.3.8.1 Differences in Merge Processing in COBOL Intermediate Actions DA 4.2

Releases 4.2 of ETI•EXTRACT and COBOL Intermediate Actions DA 4.2 (COBOL/IA DA 4.2) provide the user much better control on how data is merged than in previous releases of the DSL and Intermediate Actions. (For details please refer to the sections beginning with “Merge Processing” in Chapter 16 of the *ETI Data System Library DA: Procedures* manual.)

Given the enhanced merge control now provided, the merge processing now differs from the merge in prior releases of COBOL Intermediate Actions DA, which means that existing conversions may exhibit different behavior when the DSL for COBOL/DB2 DA is installed:

Prior to 4.2, users controlled the order of processing joins through the definition of a driver unit. The driver was specified for the target unit that was populated from a merge. The driver unit determined both the sequence in which the merges were performed, and which join unit would be used to drive each individual merge operation.

The rule of thumb in COBOL Intermediate Actions DA 4.2 is that the “**To**” (child/many) unit is the **driver in each merge operation**. When multiple merge operations are required, the driver unit can change from merge to merge. Therefore, ETI™ recommends that you *not select a driver unit* when using COBOL Intermediate Actions DA 4.2 or later and that you **use the join sequence numbers and the child unit in the relationship as the driver instead** (see “Driver Unit Specified for the Target Unit (Not Recommended)” in Chapter 16 of the *ETI Data System Library DA: Procedures* manual.). You have more control over the order of processing joins using these features.

4.3.8.2 Using Prior Releases of COBOL Intermediate Actions DA for Merge Processing

Customers that want to continue using the prior merge processing can still do so. You might want to do this if you have existing conversions that produce merges and you do not want to introduce the new merge processing yet.

Note: ETI recommends using the 4.2 merge processing unless you have existing conversions which will require the 4.1 processing.

- The following Template Definitions are included with this DSL:

```
cobol_merge41_da
cobol_sh_m_cmp41_da
cobol_sh_m_exe41_da
cobol_sh_m_std41_da
jcl_mrg_cmp41_da
jcl_mrg_exe41_da
jcl_mrg_std41_da.
```

These Template Definitions will be loaded automatically when you install the DSL components. If you load this DSL into a MetaStore™ that does not already contain COBOL Intermediate Actions DA 4.1, the template definitions will be empty. If you load this DSL into a MetaStore that does contain COBOL Intermediate Actions DA 4.1, the template definitions will be populated with the COBOL Intermediate Actions DA 4.1 Template Libraries. If you later load a DSL that includes COBOL Intermediate Actions DA 4.1 into the MetaStore, these Template Definitions will be updated to include the COBOL Intermediate Actions DA 4.1 Template Libraries.

- To use the 4.1 merge template definitions, you will need to specify these new templates as your merge intermediate action (see “Attaching Intermediate Action Templates” in Chapter 1 of the *ETI Data System Library DA: Procedures* manual), which may require you to set up additional installations.

4.3.9 Setting the Driver Unit

Setting the driver unit is typically no longer necessary. For details please refer to the sections “Driver Unit Specified for the Target Unit (Not Recommended)” and “Driver Unit Specified for a Relationship (Rarely Necessary)” in Chapter 16 “Data Relationships and Intermediate Actions” of the *ETI Data System Library DA: Procedures* manual.

4.4 Issues Addressed in Release 4.2.1

This release also contains bug fixes reported in prior versions of the DSL. The following issues are addressed:

- Beginning with Release 4.2.1, the DSL for COBOL/DB2 DA is designed to generate single-step conversion programs by default if at all possible.
- Several issues for bulk load have been addressed.
- The table lookup transform filter is now available at the database level.
- Virtual parts now function correctly as documented.
- Several properties have been added to allow the user to control sign and justification options for the string equivalent of a number function. See the “ETI Data System Library: DA Procedures, Chapter 11, Transforming Data” section of the *ETI Data System Library DA: Documentation Addendum* for details.
- Filter Modifications: several filters have been modified to correct reported filter problems.
- Update and Replace Count Changes. Update and replace counts are now maintained and reported in separate messages.

- Lookup return parts are now initialized when NULL. Previously, the return part was not initialized when NULL and as a result, the part value contained the value of the previous part.
- A new Select distinct option has been added for selecting records conditionally for the Read operations.
- A new option for connecting to a DB2 database using a particular userid and password has been added.

A complete list of CRs (software problems) fixed in this release can be provided by the AnswerLine upon request.

5 RELEASE 4.2.0

Not applicable, since 4.2.1 is the first Generally Available 4.2 release of the DSL for COBOL/DB2 DA.